




EM-TOUCH-S24

Fanless Industrial Panel PC



Specification

LCD panel	24" TFT LCD, Full HD 1920 x 1080, Anti-glare Glass / Display Glass
	250 cd/m ² , Contrast 1000:1, View angle 178°
	Touch glass - capacitive technology (non-touch as option)
Chassis	Colour: black / on request
	Material: milled aluminium, IP20/50 protected, front panel IP65 (TBD)
	Dimensions (L x H x W): 583 x 351 x 66mm
	Weight netto: TBD
Mainboard	mini-STX form factor (Fujitsu D3544-Sx) 140 x 148mm
	1x SSD m.2 2280, 1x DDR4 SO-DIMM
	Integrated I/O shield, LVDS, eDP, m.2 2230 for WLAN/BT module
Bottom panel	Power button with LED backlight
	2x DisplayPort V1.2a, 2x GLAN, 4x USB 2.0
	2x COM serial port (optional), 2x USB 3.1 gen1 (optional)
	AC Input 110-240V / DC Input 8V - 24V (optional)
Mounting options	Wall mount
	VESA holder
	other customization: (min. 20 pcs)




All product specifications are subject to change without notice.



Mainboard

D3544-S mini-STX



Powered by Intel® embedded Gemini Lake SoC (System on Chip)
10W TDP, Operating temp -30C to +50C

Supported Memory	1x DDR4 2400 SDRAM (SO-DIMM), max 16GB
CPU options	Intel® Celeron® Processor J4005 (DC @2.7GHz) integrated Intel® UHD Graphics 600 (12EUs @700MHz)
	Intel® Celeron® Processor J4105 (QC @2.5GHz) integrated Intel® UHD Graphics 600 (12EUs @750MHz)
	Intel® Pentium® Silver Processor J5005 (QC @2.8GHz) integrated Intel® UHD Graphics 605 (18EUs @800MHz)
I/O Interface	2x DisplayPort V1.2a
	Dual Channel LVDS (24Bit) and eDP V1.4 onboard
	8 Bit GPIO & HD Audio onboard
	4x USB 2.0 and 2x USB 3.1 (gen1)
	2x SATA III
	Onboard support for M.2 SSD (SATA/PCIe)
	Onboard support for M.2 WLAN/Bluetooth module
Product features	Dual GbE LAN onboard (Intel i210/Realtek RTL8111G)
	RS-232/485/422 support onboard (TBD)
	Intel® integrated TPM V2.0 onboard
	WideRange internal/external DC Input (8V - 24V)
	HW Watchdog onboard



All product specifications are subject to change without notice.